



**NOTES**

1. INDICATES NOT USED
2. N/U = NOT USED ON PLAYFIELD
3. \* INDICATES AID TEST POINT
4. COIL DIODES ARE IN4004, (E-587-6) SWITCH DIODES ARE IN 4148, (E-587-14) ALL CAPACITORS ARE .05 MFD. (E-586-80)
5. GERMANY ONLY - CAPACITOR 01 MFD. @ 500V. (E-586-65)

**PLAYFIELD A6**

- 20 A5J2-2 TO AUX. EXPANDER J1-2
- 12 A5J2-14 TOP SAUCER LANE ARROW
- 23 A5J2-15 RIGHT SAUCER ARROW
- 98 A5J2-20 TRIPLE PLAYFIELD SCORES
- 10 A5J2-6 IN SEQUENCE
- 91 A5J2-7 EXTRA BALL
- 60 A5J2-1 BONUS SPECIAL
- 34 A5J2-16 DOUBLE PLAYFIELD SCORES

REMOVE ALL BURRS

TOLERANCES ON DIMENSIONS UNLESS OTHERWISE SPECIFIED: FRACTIONS - .064 DECIMALS - .001 ANGLES -

DATE: 5-3-81

WIRING DIAGRAM PLAYFIELD

FATHOM

Bally MANUFACTURING CORP. 2640 BELMONT AVENUE CHICAGO ILLINOIS # 1233

ASSEMBLY NO. USED ON W: W-1192-30